

**RECEIVED  
CENTRAL FAX CENTER**Application Serial No. 10/564,770  
Reply to Office Action of June 11, 2008

DEC 11 2008

PATENT  
Docket: CU-4646**Amendments to the Claims**

The listing of claims presented below replaces all prior versions, and listings, of claims in the application.

**Listing of claims:**

1. **(Previously Presented)** A vertically adjustable fixture adapted to be secured to an overhead surface, comprising a base member adapted to be secured to a surface, a flexible elongated member retractable in and extendable out of said base member, a rotatable reel provided in said base member with said elongated member being partly wound around said reel, and a stationary locking mechanism provided in said base member and remotely of said reel, said locking mechanism being adapted in a locked position to lock said elongated member with respect to said base member, with said elongated member being selectively displaceable to disengage said locking mechanism to an unlocked position thereby allowing said elongated member to be displaced relative to said base member by selectively retracting said elongated member into, or withdrawing it from, said base member.
2. **(Previously Presented)** A vertically adjustable fixture as defined in Claim 1, wherein said locking mechanism is provided at a lower end of said base member, said elongated member including a series of spaced apart enlargements distributed thereon, said locking mechanism being adapted to engage in said locked position at least one of said enlargements thereby preventing said elongated member from further unwinding from said reel.
3. **(Original)** A vertically adjustable fixture as defined in Claim 2, wherein said enlargements include beads that are substantially equally spaced one after the other.
4. **(Original)** A vertically adjustable fixture as defined in Claim 3, wherein said elongated member comprises a string extending through said beads, said beads being fixedly mounted to said string.

Application Serial No. 10/564,770  
Reply to Office Action of June 11, 2008

PATENT  
Docket: CU-4646

5. **(Original)** A vertically adjustable fixture as defined in Claim 2, wherein said locking member includes a receiving means adapted to receive therein one of said enlargements, said elongated member between said enlargements thereof being slidable in and out of said receiving means when said one of said enlargements is dislodged from said receiving means.

6. **(Previously Presented)** A vertically adjustable fixture as defined in Claim 5, wherein said receiving means comprise an angled retention element that opens up onto an opening defined at said lower end of said base member and through which said elongated member extends.

7. **(Original)** A vertically adjustable fixture as defined in Claim 6, wherein said retention element comprises a recess adapted to receive said one of said beads, and a notch joining said opening and a bottom of said recess, said elongated member between said enlargements thereof being slidable in and out of said recess via said notch, wherein in said locked position said one bead is lodged in said recess with gravity forces acting downwardly on said elongated member retaining said one bead in said recess, and wherein, to disengage said one bead from said locking member, said gravity forces are sufficiently opposed for allowing said one bead to be removed from said recess thereby allowing said elongated member to be wound around, or unwound from, said reel for changing an elevation of an article suspended by said elongated member.

8. **(Original)** A vertically adjustable fixture as defined in Claim 6, wherein said retention element comprises a pair of spaced apart fingers defining a gap therebetween which communicates at one end thereof with said opening and which is sufficiently closed at an opposed end thereof, said elongated member between said enlargements thereof being adapted to be received in said gap while said one bead is supported by said fingers, wherein in said locked position said one bead is supported by said fingers gravity forces acting downwardly on said elongated member retaining said one bead on said fingers, and wherein, to disengage said one bead from said locking member, said gravity forces are sufficiently opposed for allowing said one bead to be withdrawn from

Application Serial No. 10/564,770  
Reply to Office Action of June 11, 2008

PATENT  
Docket: CU-4646

said fingers thereby allowing said elongated member to be wound around, or unwound from, said reel for changing an elevation of an article suspended by said elongated member.

9. **(Original)** A vertically adjustable fixture as defined in Claim 8, wherein said fingers are angled downwardly in a direction away from said opening of said base member.

10. **(Original)** A vertically adjustable fixture as defined in Claim 1, wherein a shaft is fixedly mounted in said base member, said reel being rotatable about said shaft, a biasing means being provided between said reel and a fixed part of one of said base member and said shaft, said biasing means being adapted to encourage winding of said elongated member around said reel.

11. **(Original)** A vertically adjustable fixture as defined in Claim 2, wherein a shaft is fixedly mounted in said base member, said reel being rotatable about said shaft, a biasing means being provided between said reel and a fixed part of one of said base member and said shaft, said biasing means being adapted to encourage winding of said elongated member around said reel, said biasing means exerting a spring force less than a downward force exerted on said reel by an article suspended from said elongated member, whereby in a suspended position of the article, said locking mechanism retains said one of said enlargements in said locked position, whereas to disengage said one bead from said locking member, said downward forces are sufficiently opposed to allow said elongated member to assume said unlocked position thereby allowing said elongated member to be wound around, or unwound from, said reel for changing an elevation of the article.

12. **(Original)** A vertically adjustable fixture as defined in Claim 10, wherein a shaft flange is provided on said shaft outwardly of said reel, said reel including a hub for receiving windings of said elongated member therearound, said hub being rotatably mounted around said shaft, first and second reel flanges being provided at opposed ends of said hub for retaining said windings around said hub.

Application Serial No. 10/564,770  
Reply to Office Action of June 11, 2008

PATENT  
Docket: CU-4646

13. **(Original)** A vertically adjustable fixture as defined in Claim 12, wherein said hub is of frusto-conical shape.

14. **(Original)** A vertically adjustable fixture as defined in Claim 12, wherein a wall extends between said shaft flange and said first reel flange thereby defining a chamber, said biasing means extending in said chamber between said reel and said fixed part.

15. **(Original)** A vertically adjustable fixture as defined in Claim 14, wherein said biasing means comprises a coiled spring.

16. **(Original)** A vertically adjustable fixture as defined in Claim 14, wherein said shaft includes said fixed part.

17. **(Original)** A vertically adjustable fixture as defined in Claim 10, wherein an opening is defined at a lower end of said base member, said elongated member extending through said opening, said shaft being off-center with respect to said opening for providing a proper orientation to said elongated member at, and/or adjacent to, said locking member.

18. **(Original)** A vertically adjustable fixture as defined in Claim 1, wherein a marking is provided on an outside surface of said base member for indicating to a user at least one direction in which said elongated member is to be displaced to move said locking mechanism to said unlocked position.

19. **(Original)** A vertically adjustable fixture as defined in Claim 10, wherein an opening is defined at a lower end of said base member, said elongated member extending through said opening, said shaft being off-center with respect to said opening for providing a proper orientation to said elongated member at, and/or adjacent to, said locking member.

Application Serial No. 10/564,770  
Reply to Office Action of June 11, 2008

PATENT  
Docket: CU-4646

20. **(Original)** A vertically adjustable fixture as defined in Claim 19, wherein a marking is provided on an outside surface of said base member for indicating to a user at least one direction in which said elongated member is to be displaced to move said locking mechanism to said unlocked position.

21. **(Original)** A vertically adjustable fixture as defined in Claim 20, wherein said shaft is angled with respect to a vertical plane extending through a portion of said elongated member which extends outwardly of said base member and along said direction.

22. **(Previously Presented)** A vertically adjustable fixture as defined in Claim 1, wherein a connector is provided at an end of said elongated member, which is located outside of said base member, said connector being adapted for suspending an item therefrom.

23. **(Previously Presented)** A vertically adjustable fixture adapted to be secured to an overhead surface, comprising a base member adapted to be secured to a surface, a flexible elongated member retractable in and extendable out of said base member, and a stationary locking mechanism provided in said base member and adapted in a locked position to lock said elongated member with respect to said base member, with said elongated member being selectively displaceable to disengage said locking mechanism to an unlocked position thereby allowing said elongated member to be displaced relative to said base member by selectively retracting said elongated member into, or withdrawing it from, said base member.

24. **(Currently Amended)** A vertically adjustable fixture adapted to be secured to an overhead surface, comprising a base member adapted to be secured to a surface, and a flexible elongated member retractable in and extendable out of said base member, said base member including a fixed member adapted to be mounted to the surface, a mobile member and a stationary locking member, said locking member being adapted in a locked position thereof to lock said mobile member to said fixed member and being adapted in an unlocked position thereof to allow said mobile to displace relative to said